

Test Report

NO. : W22816

DATE : 2015.04.21

[illegible]

Inspection item	D	T	H	U	C	K				
Basic dimension	202.00	20.00	30.000	19.00	0.60	0.00				
Tolerance (-)	201.80	19.95	30.005	18.90	0.50	0.00				
Tolerance (+)	202.20	20.05	30.012	19.10	0.70	0.00				
Measured value	202.16	20.02	30.008	20.04	0.57					

[illegible][illegible]

Inspection item	V1	V2	V3	V4	V5	V6	V7	V8	V9	V10	V11	V12							
Basic dimension	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'	45°00'							
Tolerance (-)	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'	44°30'							
Tolerance (+)	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'	45°30'							
Measured value	44°37'	44°52'	44°59'	45°01'	45°04'	44°58'	45°10'	45°03'	45°04'	44°57'	44°57'	44°32'							

Inspection item	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12					
Basic dimension	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20					
Tolerance (-)	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18	0.18					
Tolerance (+)	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22					
Measured value	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22					

[illegible][illegible]

Swing		Right side	Left side	Periphery			Unbalance amount
Tolerance (Max)		0.005	0.005	0.010			0.20g
Measured value		0.005	0.003	0.002			0.07g

